S4 Universal Mounting System

The smart, certified, and patented solution for solar without compromise.

VERSION 26.10.02 - OCT 19TH 2026

S4 RooFit

One system. All panel sizes.

Portrait or Landscape. No Limitation.

VERTICAL EXTENSION SYSTEM

Full compatibility with all Panel Heights

HORIZONTAL EXTENSION SYSTEM

FULL COMPATIBILITY WITH ALL PANEL WIDTHS

Durability exceeding 25 years
10 Year Warranty

BBA CERTIFICATE BBA 7468

BBA APPROVAL INSPECTION TESTING CERTIFICATION CERTIFICATE 25/7499

MCS012 Certified
Since Sep 2025

NHBC Compliance
BBA Certified

S4 Universal Mounting System

The smart, certified, and patented solution for solar without compromise.

Only 7 accessories needed

STAINLESS STEEL SCREW FOR CLAMPS
6.5 X 60MM + EPDM WASHER

SINGLE CLAMP WITH EPDM

DOUBLE CLAMP WITH EPDM

ALUMINIUM UNIVERSAL
INTERMODULE BLACK

UK – MANDATORY BETWEEN
TWO MODULES FOR MCS COMPLIANCE

FLASHING HOOKS



LATERAL FLASHING

HEXAGONAL HEAD SCREW
6.5 x 25 MM FOR FIXING THE PLATE.

Key Advantages

1. Full height universality
Adapts to all panel heights from legacy models tofuture generations thanks to modular vertical extensions.

2. Full width universality
Universal horizontal extensions fit every panel widthwith no format limitation.

3. Guaranteed compatibility for decades
Future-proof design ensures long-term continuityeven as panel standards evolve.

4. Simplified panel replacement
If panel sizes change, only the modules are replacedwhile the S4 Roofit base stays intact.

5. Portrait or landscape orientation
Both orientations possible without extra parts oradded cost, offering total on-site freedom.

6. No top flashing required
BBA tested and approved design . No top flashing required, suitable for roof pitches from 12° to 70°

7. Only six components in total
Ultra-simplified design reduces costs, errors, andlogistics complexity.

8. Mixed orientations on the same roof
Combine portrait and landscape panels to optimizeevery surface.

9. No battens in portrait mode
Direct fixing streamlines preparation and accelerates installation.

10. Reduced battens in landscape mode
Only one horizontal batten is needed between rowsfor secure and efficient fixing.

Technical Features

- Colour accessories Black (100% recyclable)
- Material PP Aluminium Stainless Steel (100% recyclable)
- Temperature Range Utilisation -20° + 85°
- Pitch 12° to 70°
- Public liability Insurance BB European Group SE

S4 MOUNTING SYSTEM FRANCE
55 Avenue Marceau 75116 Paris
TEL : +33 9 55 17 82 59
RCS: 911 110 773 RCS Paris
Mail: contact@S4mountingsystem.com

UK - TRAINING CENTRE & SUPPORT
Unit 4A, Silverwoods Trade Park
Kidderminster, Worcestershire
DY11 7GB, United Kingdom
Phone : +44 7912 285918 contact@S4mountingsystem.co.uk